
ABCD - ILE DE RE - UV LACK
A16355



Maßtafel	
LÄNGE	1900 mm
BREITE	190 mm
GESAMTSTÄRKE	14.0 mm
STÄRKE NUTZSCHICHT	3 mm
INHALTSVERZEICHNIS	Min 6 Pl x 1900 mm

Maßpaket	
PACKUNGSLÄNGE	1950 mm
PACKUNGSBREITE	200 mm
PACKUNGSSTÄRKE	121 mm
PACKUNGSGEWICHT	23 kg
STÜCK/PAKET	8
M²/PAKET	2.89 m²

Abmessung Palette	
PALETTENLÄNGE	1950 mm
PALETTENBREITE	1000 mm
PALETTENHÖHE	1080 mm
PALETTENGEWICHT	1075 kg
PAKETE/PALETTE	45
M²/PALETTE	130.05 m²

© This fact sheet was written by Labeco BVBA, Sprietestraat 326, B-8792 Waregem. Text, photographs, drawings, tables , graphs should in no way be distributed , used or copied unless LABECO BVBA has granted reproduction rights. At the moment of establishment of the sheet, all information is specified correctly. The company reserves the right to change the specifications of the product at any time without prior notice to third parties. The photographs, drawings, tables , graphs used in this sheet are intended only as illustrations. No rights can be derived from them.

ABCD - ILE DE RE - UV LACK
A16355

MERKMALE

Oberste Schicht

HOLZART	Eiche
LATEINISCHER NAME	Quercus Robur
SORTIERUNG	ABCD
AUFBAU	3-lagig
STÄRKE NUTZSCHICHT	3 mm
DEKOR	1 Streifen
SCHNITTART	Sägefurnier
FASENART	2 Längsseiten 0,75 mm gefast
AUSFÜHRUNG	Lack
OBERFLÄCHENSTRUKTUR	Gebürstet

Zusammensetzung des Trägers

TRÄGERART	Pappel
HOLZART TRÄGER	Populier
GESAMTSTÄRKE TRÄGER	11 mm
VERLEIMUNG	Kruiselings

Einrichtung

SYSTEM

Dropclick

ANWENDUNGEN

Leichte Nutzung im Haushalt.
Mäßige gewerbliche Nutzung.
Normale gewerbliche Nutzung.
Normale Nutzung im Haushalt.
Intensive gewerbliche Nutzung.

FUßBODENHEIZUNG

Ja

ABSCHLEIFBAR

Ja

© This fact sheet was written by Labeco BVBA, Sprietestraat 326, B-8792 Waregem. Text, photographs, drawings, tables , graphs should in no way be distributed , used or copied unless LABECO BVBA has granted reproduction rights. At the moment of establishment of the sheet, all information is specified correctly. The company reserves the right to change the specifications of the product at any time without prior notice to third parties. The photographs, drawings, tables , graphs used in this sheet are intended only as illustrations. No rights can be derived from them.

ABCD - ILE DE RE - UV LACK
A16355

TECHNISCHE DATEN

	Norm	Ergebnis
REAKTION AUF FEUER	EN 13501-1	Dfl-S1
FORMALDEHYD-EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
WÄRMELEITFÄHIGKEIT	EN 12667 / ISO 8302	0,11m² k/w
BIOLOGISCHE DAUERHAFTIGKEIT	EN 335	Klasse 1
BRUCHFESTIGKEIT	EN 1533	Pass
SCHLÜPFRIGKEIT	EN 15676	Pass
FEUCHTIGKEITSGEHALT	EN 13183-1	7% (+/-2%)

ZERTIFIZIERUNG

CE

EN 14342

ÉMISSIONS DANS L'AIR INTÉRIEUR A+ A+ A B C

Highly recommended for living areas. AgBB -tested

CODE FOR A SUSTAINABLE BUILT ENVIRONMENT BREEAM

© This fact sheet was written by Labeco BVBA, Sprietestraat 326, B-8792 Waregem. Text, photographs, drawings, tables , graphs should in no way be distributed , used or copied unless LABECO BVBA has granted reproduction rights. At the moment of establishment of the sheet, all information is specified correctly. The company reserves the right to change the specifications of the product at any time without prior notice to third parties. The photographs, drawings, tables , graphs used in this sheet are intended only as illustrations. No rights can be derived from them.