# ABC - NATURAL - UV LACQUER
## V17286

### Maßtafel

| | |
|---|---|
| **LÄNGE** | 1200 mm |
| **BREITE** | 90 mm |
| **GESAMTSTÄRKE** | 14.0 mm |
| **STÄRKE NUTZSCHICHT** | 3 mm |

### Maßpaket

| | |
|---|---|
| **PACKUNGSLÄNGE** | 1250 mm |
| **PACKUNGSBREITE** | 195 mm |
| **PACKUNGSSTÄRKE** | 115 mm |
| **PACKUNGSGEWICHT** | 19 kg |
| **STÜCK/PAKET** | 8 |
| **M²/PAKET** | 1.73 $m^2$ |

### Abmessung Palette

| | |
|---|---|
| **PALETTENLÄNGE** | 1250 mm |
| **PALETTENBREITE** | 1150 mm |
| **PALETTENHÖHE** | 1080 mm |
| **PALETTENGEWICHT** | 930 kg |
| **PAKETE/PALETTE** | 48 |
| **M²/PALETTE** | 83.04 $m^2$ |

## MERKMALE

### Oberste Schicht

| | |
|---|---|
| **HOLZART** | Eiche |
| **LATEINISCHER NAME** | Quercus Robur |
| **SORTIERUNG** | ABC |
| **AUFBAU** | 2-laags |
| **STÄRKE NUTZSCHICHT** | 3 mm |
| **DEKOR** | 1 Streifen |
| **SCHNITTART** | Sägefurnier |
| **FASENART** | 2 Längsseiten 0,75 mm gefast |
| **AUSFÜHRUNG** | Lack |
| **OBERFLÄCHENSTRUKTUR** | Gebürstet |

### Zusammensetzung des Trägers

| | |
|---|---|
| **TRÄGERART** | Multiplex |
| **GESAMTSTÄRKE TRÄGER** | 11 mm |

### Einrichtung

**SYSTEM**

T&G

**ANWENDUNGEN**

Leichte Nutzung im Haushalt.
Mäßige gewerbliche Nutzung.
Normale gewerbliche Nutzung.
Normale Nutzung im Haushalt.
Intensive gewerbliche Nutzung.

**FUßBODENHEIZUNG**

Ja

**ABSCHLEIFBAR**

Nein

© This fact sheet was written by Labeco BVBA, Sprietestraat 326, B-8792 Waregem. Text, photographs, drawings, tables , graphs should in no way be distributed , used or copied unless LABECO BVBA has granted reproduction rights. At the moment of establishment of the sheet, all information is specified correctly. The company reserves the right to change the specifications of the product at any time without prior notice to third parties. The photographs, drawings, tables , graphs used in this sheet are intended only as illustrations. No rights can be derived from them.

# ABC - NATUR - UV LACK
**V17286**

## TECHNISCHE DATEN

| | Norm | Ergebnis |
|---|---|---|
| **REAKTION AUF FEUER** | EN 13501-1 | Dfl-S1 |
| **FORMALDEHYD-EMISSION** | EN 717-1 | E1 |
| **PCP** | CEN/TR 14823 | ≤ 5ppm |
| **WÄRMELEITFÄHIGKEIT** | EN 12667 / ISO 8302 | 0,11m² k/w |
| **BIOLOGISCHE DAUERHAFTIGKEIT** | EN 335 | Klasse 1 |
| **BRUCHFESTIGKEIT** | EN 1533 | Pass |
| **SCHLÜPFRIGKEIT** | EN 15676 | Pass |
| **FEUCHTIGKEITSGEHALT** | EN 13183-1 | 7% (+/-2%) |

## ZERTIFIZIERUNG

CE

EN 14342

ÉMISSIONS DANS L'AIR INTÉRIEUR A+ A+ A B C

Highly recommended for living areas. AgBB -tested

CODE FOR A SUSTAINABLE BUILT ENVIRONMENT BREEAM

© This fact sheet was written by Labeco BVBA, Sprietestraat 326, B-8792 Waregem. Text, photographs, drawings, tables , graphs should in no way be distributed , used or copied unless LABECO BVBA has granted reproduction rights. At the moment of establishment of the sheet, all information is specified correctly. The company reserves the right to change the specifications of the product at any time without prior notice to third parties. The photographs, drawings, tables , graphs used in this sheet are intended only as illustrations. No rights can be derived from them.