CLASSIC - BRUT
A13211



Dimension board

LENGTH	2200 mm
WIDTH	220 mm
TOTAL THICKNESS	21.0 mm
THICKNESS TOP LAYER	6 mm
LAYER CONTENTS	Min 3 Pl x 2200 mm

Dimension pack

PACK LENGTH	2210 mm
PACK WIDTH	230 mm
PACK THICKNESS	95 mm
PACK WEIGHT	28 kg
LAYERS/BOX	4
M²/PACK	1.94 m²

Dimension pallet

PALLET LENGTH	2230 mm
PALLET WIDTH	920 mm
PALLET HEIGHT	1070 mm
PALLET WEIGHT	1120 kg
PACKS/PALLET	40
M²/PALLET	77.60 m²

CHARACTERISTICS

Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	CLASSIC
CONSTRUCTION	2-laags
THICKNESS TOP LAYER	6 mm
PATTERN	1 strip
CUTTING METHOD	Zaagfineer
BEVEL	Micro bevel 2 long sides
SURFACE STRUCTURE	Smooth

Composition of the support

SUPPORT TYPE	MPX
WOOD SPECIES SUPPORT	Mixed Light Hardwood
TOTAL THICKNESS SUPPORT	15 mm
ADHESION	Kruiselings

Installation

SYSTEM

Tongue and groove

APPLICATIONS

Light household use.
Moderate commercial use.
Normal commercial use.
Normal household use.
Intensive commercial use.

UNDERFLOOR HEATING

No

RE-SANDABLE

Yes

© This fact sheet was written by Labeco BVBA, Sprietestraat 326, B-8792 Waregem. Text, photographs, drawings, tables , graphs should in no way be distributed , used or copied unless LABECO BVBA has granted reproduction rights. At the moment of establishment of the sheet, all information is specified correctly. The company reserves the right to change the specifications of the product at any time without prior notice to third parties. The photographs, drawings, tables , graphs used in this sheet are intended only as illustrations. No rights can be derived from them.

CLASSIC - BRUT
A13211

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION

EN 14342

© This fact sheet was written by Labeco BVBA, Sprietestraat 326, B-8792 Waregem. Text, photographs, drawings, tables , graphs should in no way be distributed , used or copied unless LABECO BVBA has granted reproduction rights. At the moment of establishment of the sheet, all information is specified correctly. The company reserves the right to change the specifications of the product at any time without prior notice to third parties. The photographs, drawings, tables , graphs used in this sheet are intended only as illustrations. No rights can be derived from them.