



Dimension board	
LENGTH	1900 mm
WIDTH	158 mm
TOTAL THICKNESS	14.0 mm
THICKNESS TOP LAYER	3 mm
LAYER CONTENTS	Min 7Pl x 1900

Dimension pack	
PACK LENGTH	1910 mm
PACK WIDTH	160 mm
PACK THICKNESS	120 mm
PACK WEIGHT	22 kg
LAYERS/BOX	8
M ² /PACK	$2.40 \ m^2$

1930 mm
1000 mm
1080 mm
1100 kg
54
129.60 m ²

CHARACTERISTICS

_			
н.	\sim	lay	IOT
111	OD	Ia\	/ 🖯 🗆

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	CLASSIC B
CONSTRUCTION	3-layer
THICKNESS TOP LAYER	3 mm
PATTERN	1 strip
CUTTING METHOD	Zaagfineer
BEVEL	Micro bevel 4 sides
FINISH	Hardwax oil
SURFACE STRUCTURE	Antique

Composition of the support

SUPPORT TYPE	Populier
WOOD SPECIES SUPPORT	Populier
TOTAL THICKNESS SUPPORT	11 mm
ADHESION	Kruiselings

Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Drop click	Light household use.	Yes
	Moderate commercial use.	
	Normal commercial use.	RE-SANDABLE
	Normal household use.	Yes
	Intensive commercial use	





TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION









