

SOLID FLOORING 20X200X500-2200 RANDOM LENGTHS - BRUT A14426

Dimension board

LENGTH	2200 mm
WIDTH	200 mm
TOTAL THICKNESS	20.0 mm
LAYER CONTENTS	Random Lengths

Dimension pack

PACK LENGTH	2250 mm
PACK WIDTH	205 mm
PACK THICKNESS	105 mm
PACK WEIGHT	29 kg
LAYERS/BOX	5
M ² /PACK	2.20 m ²

Dimension pallet

PALLET LENGTH	2250 mm
PALLET WIDTH	925 mm
PALLET HEIGHT	825 mm
PALLET WEIGHT	1750 kg
PACKS/PALLET	45
M ² /PALLET	99.00 m ²

CHARACTERISTICS

Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	CLASSIC
PATTERN	1 strip
CUTTING METHOD	Zaagfineer
BEVEL	Micro bevel 4 sides
SURFACE STRUCTURE	Smooth

Composition of the support

ADHESION	Kruiselings
----------	-------------

Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	Licht huishoudelijk gebruik. Matig commercieel gebruik. Neem de nodige maatregelen voor gebruik in vochtige ruimtes. Normaal commercieel gebruik. Normaal huishoudelijk gebruik. Overvloedig commercieel gebruik.	No RE-SANDABLE Yes

SOLID FLOORING 20X200X500-2200 RANDOM LENGTHS - BRUT

TECHNICAL SPECIFICATIONS

A14426

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION



EN 14342

