



Dimension board

LENGTH	2200 mm
WIDTH	240 mm
TOTAL THICKNESS	14.0 mm
THICKNESS TOP LAYER	3 mm
LAYER CONTENTS	2x 2200mm // 2x RL

Dimension pack

PACK LENGTH	2200 mm
PACK WIDTH	250 mm
PACK THICKNESS	60 mm
PACK WEIGHT	23 kg
LAYERS/BOX	4
M²/PACK	2.11 m ²

Dimension pallet

PALLET LENGTH	2200 mm
PALLET WIDTH	1000 mm
PALLET HEIGHT	1150 mm
PALLET WEIGHT	1460 kg
PACKS/PALLET	64
M²/PALLET	135.04 m ²

CHARACTERISTICS

Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	AB
CONSTRUCTION	2-laags
THICKNESS TOP LAYER	3 mm
PATTERN	1 strip
CUTTING METHOD	Zaagfineer
BEVEL	Micro bevel 4 sides
FINISH	Untreated
SURFACE STRUCTURE	Smooth

Composition of the support

SUPPORT TYPE	MPX
WOOD SPECIES SUPPORT	Berk
TOTAL THICKNESS SUPPORT	10 mm
ADHESION	Kruiselings

Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	Light household use. Moderate commercial use. Normal commercial use. Normal household use. Intensive commercial use.	Yes RE-SANDABLE No

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION



EN 14342

