# ABC - NATURAL - UV OIL - XL PLANK
**A16709**




### Dimension board

| | |
|---|---|
| **LENGTH** | 3850 mm |
| **WIDTH** | 300 mm |
| **TOTAL THICKNESS** | 16.0 mm |
| **THICKNESS TOP LAYER** | 4 mm |
| **LAYER CONTENTS** | Min 3 Pl x 3850 mm |

### Dimension pack

| | |
|---|---|
| **PACK LENGTH** | 3900 mm |
| **PACK WIDTH** | 320 mm |
| **PACK THICKNESS** | 65 mm |
| **PACK WEIGHT** | 42 kg |
| **LAYERS/BOX** | 4 |
| **M²/PACK** | 4.62 m² |

### Dimension pallet

| | |
|---|---|
| **PALLET LENGTH** | 3900 mm |
| **PALLET WIDTH** | 950 mm |
| **PALLET HEIGHT** | 750 mm |
| **PALLET WEIGHT** | 1150 kg |
| **PACKS/PALLET** | 27 |
| **M²/PALLET** | 124.74 m² |

## CHARACTERISTICS

### Top layer

| | |
|---|---|
| **WOOD SPECIES** | Oak |
| **LATIN NAME** | Quercus Robur |
| **GRADE** | ABC |
| **CONSTRUCTION** | 3-layer |
| **THICKNESS TOP LAYER** | 4 mm |
| **PATTERN** | 1 strip |
| **CUTTING METHOD** | Sawn veneer |
| **BEVEL** | Bevel 2 long sides 0,75 mm |
| **FINISH** | UV Oil |
| **SURFACE STRUCTURE** | Brushed |

### Composition of the support

| | |
|---|---|
| **SUPPORT TYPE** | Spruce |
| **WOOD SPECIES SUPPORT** | Spruce |
| **TOTAL THICKNESS SUPPORT** | 14 mm |
| **ADHESION** | Kruiselings |

### Installation

**SYSTEM**

T&G

**APPLICATIONS**

Light household use.
Moderate commercial use.
Normal commercial use.
Normal household use.
Intensive commercial use.

**UNDERFLOOR HEATING**

Yes

**RE-SANDABLE**

Yes

© This fact sheet was written by Labeco BVBA, Sprietestraat 326, B-8792 Waregem. Text, photographs, drawings, tables , graphs should in no way be distributed , used or copied unless LABECO BVBA has granted reproduction rights. At the moment of establishment of the sheet, all information is specified correctly. The company reserves the right to change the specifications of the product at any time without prior notice to third parties. The photographs, drawings, tables , graphs used in this sheet are intended only as illustrations. No rights can be derived from them.

# ABC - NATURAL - UV OIL - XL PLANK
**A16709**

## TECHNICAL SPECIFICATIONS

| | Norm | Result |
|---|---|---|
| **REACTION TO FIRE** | EN 13501-1 | Dfl-S1 |
| **FORMALDEHYDE EMISSION** | EN 717-1 | E1 |
| **PCP** | CEN/TR 14823 | ≤ 5ppm |
| **THERMAL CONDUCTIVITY** | EN 12667 / ISO 8302 | 0,11m² k/w |
| **BIOLOGICAL DURABILITY** | EN 335 | Class 1 |
| **BREAKING STRENGTH** | EN 1533 | Pass |
| **SLIPPERINESS** | EN 15676 | Pass |
| **MOISTURE CONTENT** | EN 13183-1 | 7% (+/-2%) |

## CERTIFICATION

EN 14342

© This fact sheet was written by Labeco BVBA, Sprietestraat 326, B-8792 Waregem. Text, photographs, drawings, tables , graphs should in no way be distributed , used or copied unless LABECO BVBA has granted reproduction rights. At the moment of establishment of the sheet, all information is specified correctly. The company reserves the right to change the specifications of the product at any time without prior notice to third parties. The photographs, drawings, tables , graphs used in this sheet are intended only as illustrations. No rights can be derived from them.