

Dimension board

LENGTH	2200 mm
WIDTH	180 mm
TOTAL THICKNESS	14.0 mm
THICKNESS TOP LAYER	3 mm
LAYER CONTENTS	Min 3 Pl x 2200 mm

Dimension pack

PACK LENGTH	2250 mm
PACK WIDTH	185 mm
PACK THICKNESS	84 mm
PACK WEIGHT	23 kg
LAYERS/BOX	6
M ² /PACK	2.38 m ²

Dimension pallet

PALLET LENGTH	2250 mm
PALLET WIDTH	950 mm
PALLET HEIGHT	1100 mm
PALLET WEIGHT	1280 kg
PACKS/PALLET	55
M²/PALLET	130.90 m ²

CHARACTERISTICS

Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	AB
CONSTRUCTION	2-layer
THICKNESS TOP LAYER	3 mm
PATTERN	1 strip
CUTTING METHOD	Zaagfijneer
BEVEL	4 zijden 0,75 mm velling
FINISH	Onbehandeld
SURFACE STRUCTURE	Smooth

Composition of the support

SUPPORT TYPE	MPX
WOOD SPECIES SUPPORT	Berk
TOTAL THICKNESS SUPPORT	11 mm
ADHESION	Kruiselings

Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	Light household use.	Yes
	Moderate commercial use.	
	Normal commercial use.	RE-SANDABLE
	Normal household use.	Yes
	Intensive commercial use.	

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION



EN 14342

