



Dimension board

LENGTH	2200 mm
WIDTH	180 mm
TOTAL THICKNESS	20.0 mm

Dimension pack

PACK LENGTH	2250 mm
PACK WIDTH	185 mm
PACK THICKNESS	105 mm
PACK WEIGHT	29 kg
LAYERS/BOX	5
M²/PACK	1.98 m ²

Dimension pallet

PALLET LENGTH	2250 mm
PALLET WIDTH	925 mm
PALLET HEIGHT	875 mm
PALLET WEIGHT	1305 kg
PACKS/PALLET	45
M²/PALLET	89.10 m ²

CHARACTERISTICS

Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	CLASSIC B
CONSTRUCTION	1-layer
PATTERN	1 strip
BEVEL	Micro bevel 4 sides
FINISH	Untreated
SURFACE STRUCTURE	Smooth

Composition of the support

SUPPORT TYPE	Massief hout
---------------------	--------------

Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	Light household use. Moderate commercial use. Normal commercial use. Normal household use. Intensive commercial use.	No
		RE-SANDABLE
		No

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION



EN 14342

