



Dimension board

WIDTH	120 mm
TOTAL THICKNESS	20.0 mm

Dimension pack

PACK LENGTH	2500 mm
PACK WIDTH	120 mm
PACK THICKNESS	100 mm
PACK WEIGHT	23 kg
LAYERS/BOX	5
M²/PACK	1.50 m ²

Dimension pallet

PALLET LENGTH	2500 mm
PALLET WIDTH	960 mm
PALLET HEIGHT	1050 mm
PALLET WEIGHT	1620 kg
PACKS/PALLET	72
M²/PALLET	108.00 m ²

CHARACTERISTICS

Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	CLASSIC A
CONSTRUCTION	1-layer
PATTERN	1 strip
BEVEL	Micro bevel 4 sides
FINISH	Untreated
SURFACE STRUCTURE	Smooth

Composition of the support

SUPPORT TYPE	Massief hout
---------------------	--------------

Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	Light household use. Moderate commercial use. Normal commercial use. Normal household use. Intensive commercial use.	No RE-SANDABLE Yes

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION



EN 14342

