



Dimension board

LENGTH	660 mm
WIDTH	92 mm
TOTAL THICKNESS	14.0 mm
THICKNESS TOP LAYER	3 mm
LAYER CONTENTS	6L + 6R

Dimension pack

PACK LENGTH	1400 mm
PACK WIDTH	185 mm
PACK THICKNESS	86 mm
PACK WEIGHT	10 kg
LAYERS/BOX	12
M²/PACK	0.71 m ²

Dimension pallet

PALLET LENGTH	1400 mm
PALLET WIDTH	1050 mm
PALLET HEIGHT	1050 mm
PALLET WEIGHT	1045 kg
PACKS/PALLET	110
M²/PALLET	78.10 m ²

CHARACTERISTICS

Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	CLASSIC
CONSTRUCTION	3-layer
THICKNESS TOP LAYER	3 mm
PATTERN	Hungarian point
CUTTING METHOD	Zaagfineer
BEVEL	Micro bevel 4 sides
FINISH	Lacquer
SURFACE STRUCTURE	Smooth

Composition of the support

SUPPORT TYPE	Hevea
WOOD SPECIES SUPPORT	Hevea
TOTAL THICKNESS SUPPORT	11 mm
ADHESION	Kruiselings

Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	Light household use. Moderate commercial use. Normal commercial use. Normal household use. Intensive commercial use.	Yes RE-SANDABLE Yes

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION



EN 14342

