



## Dimension board

LENGTH	1900 mm
WIDTH	150 mm
TOTAL THICKNESS	12.0 mm
THICKNESS TOP LAYER	3 mm
LAYER CONTENTS	Min 6 Pl x 1900 mm

## Dimension pack

PACK LENGTH	1910 mm
PACK WIDTH	160 mm
PACK THICKNESS	100 mm
PACK WEIGHT	18 kg
LAYERS/BOX	8
M <sup>2</sup> /PACK	2.28 m <sup>2</sup>

## Dimension pallet

PALLET LENGTH	1930 mm
PALLET WIDTH	1000 mm
PALLET HEIGHT	1080 mm
PALLET WEIGHT	1260 kg
PACKS/PALLET	54
M <sup>2</sup> /PALLET	123.12 m <sup>2</sup>

## CHARACTERISTICS

### Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	CLASSIC A
CONSTRUCTION	3-layer
THICKNESS TOP LAYER	3 mm
PATTERN	1 strip
CUTTING METHOD	Zaagfineer
BEVEL	Micro bevel 2 long sides
FINISH	Lacquer
SURFACE STRUCTURE	Brushed

### Composition of the support

SUPPORT TYPE	MPX
WOOD SPECIES SUPPORT	Mixed Light Hardwood
TOTAL THICKNESS SUPPORT	9 mm
ADHESION	Kruiselings

### Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Drop click	Light household use. Moderate commercial use. Normal commercial use. Normal household use. Intensive commercial use.	Yes
		RE-SANDABLE
		Yes

## TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m <sup>2</sup> k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

## CERTIFICATION



EN 14342

