



## Dimension board

LENGTH	660 mm
WIDTH	90 mm
TOTAL THICKNESS	14.0 mm
THICKNESS TOP LAYER	3 mm
LAYER CONTENTS	6L + 6R

## Dimension pack

PACK LENGTH	1400 mm
PACK WIDTH	185 mm
PACK THICKNESS	86 mm
PACK WEIGHT	10 kg
LAYERS/BOX	12
M <sup>2</sup> /PACK	0.71 m <sup>2</sup>

## Dimension pallet

PALLET LENGTH	1400 mm
PALLET WIDTH	1050 mm
PALLET HEIGHT	1050 mm
PALLET WEIGHT	1045 kg
PACKS/PALLET	110
M <sup>2</sup> /PALLET	78.10 m <sup>2</sup>

## CHARACTERISTICS

## Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	ABC
CONSTRUCTION	3-layer
THICKNESS TOP LAYER	3 mm
PATTERN	Hungarian point
CUTTING METHOD	Zaagfineer
BEVEL	Micro bevel 4 sides
FINISH	Lacquer
SURFACE STRUCTURE	Smooth

## Composition of the support

SUPPORT TYPE	Hevea
WOOD SPECIES SUPPORT	Hevea
TOTAL THICKNESS SUPPORT	11 mm
ADHESION	Kruiselings

## Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	Light household use. Moderate commercial use. Normal commercial use. Normal household use. Intensive commercial use.	Yes
		RE-SANDABLE
		Yes

## TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m <sup>2</sup> k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

## CERTIFICATION



EN 14342

