



Dimension board

LENGTH	1200 mm
WIDTH	150 mm
TOTAL THICKNESS	15.0 mm
THICKNESS TOP LAYER	4 mm
LAYER CONTENTS	Min 6 Pl x 1200 mm

Dimension pack

PACK LENGTH	1205 mm
PACK WIDTH	155 mm
PACK THICKNESS	125 mm
PACK WEIGHT	15 kg
LAYERS/BOX	8
M²/PACK	1.44 m ²

Dimension pallet

PALLET LENGTH	1210 mm
PALLET WIDTH	1100 mm
PALLET HEIGHT	1200 mm
PALLET WEIGHT	615 kg
PACKS/PALLET	40
M²/PALLET	57.60 m ²

CHARACTERISTICS

Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	ABCD
CONSTRUCTION	3-layer
THICKNESS TOP LAYER	4 mm
PATTERN	1 strip
CUTTING METHOD	Zaagfineer
BEVEL	Micro bevel 2 long sides
FINISH	Lacquer
SURFACE STRUCTURE	Brushed

Composition of the support

SUPPORT TYPE	Populier
WOOD SPECIES SUPPORT	Populier
TOTAL THICKNESS SUPPORT	11 mm
ADHESION	Kruiselings

Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Drop click	Light household use. Moderate commercial use. Normal commercial use. Normal household use. Intensive commercial use.	Yes RE-SANDABLE Yes

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION



EN 14342

