

Dimension board

LENGTH	1000 mm
WIDTH	1000 mm
TOTAL THICKNESS	15.0 mm
THICKNESS TOP LAYER	0 mm

Dimension pack

PACK LENGTH	1000 mm
PACK WIDTH	1000 mm
PACK THICKNESS	45 mm
PACK WEIGHT	23 kg
LAYERS/BOX	2
M ² /PACK	2.00 m ²

Dimension pallet

PALLET LENGTH	1000 mm
PALLET WIDTH	1000 mm
PALLET HEIGHT	990 mm
PALLET WEIGHT	550 kg
PACKS/PALLET	22
M ² /PALLET	44.00 m ²

CHARACTERISTICS

Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	PRIME
CONSTRUCTION	2-laags
THICKNESS TOP LAYER	0 mm
PATTERN	Versailles
BEVEL	Micro bevel 4 sides
FINISH	Untreated
SURFACE STRUCTURE	Smooth

Composition of the support

TOTAL THICKNESS SUPPORT	16 mm
-------------------------	-------

Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	Light household use. Moderate commercial use. Normal commercial use. Normal household use. Intensive commercial use.	No RE-SANDABLE Yes

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION



EN 14342

