



Size

MIN LENGTH	200 mm
MAX LENGTH	400 mm
MIN. THICKNESS	4 mm
MAX. THICKNESS	13 mm
AVERAGE THICKNESS	5 mm

Size

ROW LENGTH	mm
LENGTH	1500 mm
WIDTH	180 mm
MIN. THICKNESS	mm
MAX. THICKNESS	mm

Size Pack

PACK LENGTH	1510 mm
PACK WIDTH	185 mm
PACK THICKNESS	106 mm
LAYERS/PACK	4
M <sup>2</sup> /PACK	1.08 m <sup>2</sup>

Characteristics

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	ABC
CONSTRUCTION	Samengesteld

TOTAL THICKNESS SUPPORT	mm
SURFACE STRUCTURE	Smooth
COLOUR FINISH	Smoked Unfinished

Installation

INSTALLATION	Nail down
DIRECTION	Diagonal Horizontal

**Certification**

This product conforms to CE-standard EN 14951: Solid wood panelling and cladding

- Formaldehyde-emission, determined according to standard EN 13183-1:E1
- Moisture content, determined according to standard EN 13183-1: 10% (+/-2%). Suitable for use in dry rooms with a moisture content of 50% to 60%
- Width Shrinkage, complies with standard EN 13647
- Reaction to fire, determined according to standard EN 13501-1: D-s1, d0
- PCP (pentachloorfenol) < 5 ppm
- Density & thickness: 390, 9/5
- Water-vapour permeability: NPD
- Thermal conductivity: 0,04 W/mK
- Sound absorption: NPD
- Biological durability: Class 2

---

**Technical specifications**

Suitable for indoor use only.