



Size

MIN LENGTH	100 mm
MAX LENGTH	250 mm
MIN. THICKNESS	5 mm
MAX. THICKNESS	40 mm
AVERAGE THICKNESS	25 mm

Size

ROW LENGTH	630 mm
LENGTH	630 mm
WIDTH	200 mm
MIN. THICKNESS	mm
MAX. THICKNESS	40 mm

Size Pack

PACK LENGTH	710 mm
PACK WIDTH	420 mm
PACK THICKNESS	110 mm
LAYERS/PACK	8
M²/PACK	1.01 m ²

Characteristics

WOOD SPECIES	Teak
LATIN NAME	Tectona Grandis
GRADE	CLASSIC
CONSTRUCTION	Solid

TOTAL THICKNESS SUPPORT	mm
SURFACE STRUCTURE	Structured
COLOUR FINISH	Thermique treatment

Installation

INSTALLATION	Glue Nail down
DIRECTION	Diagonal Horizontal Vertical

Certification

This product conforms to CE-standard EN 14951: Solid wood panelling and cladding

- Formaldehyde-emission, determined according to standard EN 13183-1:E1
- Moisture content, determined according to standard EN 13183-1: 10% (+/-2%). Suitable for use in dry rooms with a moisture content of 50% to 60%
- Width Shrinkage, complies with standard EN 13647
- Reaction to fire, determined according to standard EN 13501-1: D-s1, d0
- PCP (pentachloorfenol) < 5 ppm
- Density & thickness: 390, 9/5
- Water-vapour permeability: NPD
- Thermal conductivity: 0,04 W/mK
- Sound absorption: NPD
- Biological durability: Class 1

Technical specifications

Suitable for indoor use only.