

|                                                                                                                       | STANDARD                                                     | RESULT                                                                                     |
|-----------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------|--------------------------------------------------------------------------------------------|
| Dimensions and basic data                                                                                             |                                                              |                                                                                            |
|  SIZE                                | EN ISO 24342                                                 | Plank: 225 x 1830 mm                                                                       |
|  THICKNESS                           | EN ISO 24346                                                 | 8 mm (6 mm spc + 2 mm integrated cork backing)                                             |
|  WEAR LAYER                          | EN ISO 24340                                                 | 0.70 mm                                                                                    |
| LOCKING METHOD                                                                                                        |                                                              | Click-system                                                                               |
| SURFACE TREATMENT                                                                                                     |                                                              | PU coating + protected with aluminium oxide (anti-scratch) and stain resistant technology. |
| CORE                                                                                                                  |                                                              | Sound reducing water resistant rigid core, SPC                                             |
| Technical data - CE EN 14041                                                                                          |                                                              |                                                                                            |
|  BEVELLED EDGE                       | MICRO                                                        | 4 Sides                                                                                    |
|  MASS                                |                                                              | 15.60 kg/m <sup>2</sup>                                                                    |
|  STANDARDS                          | EN 16511                                                     | Pass                                                                                       |
|  CLASSIFICATION                    | EN 685 / EN ISO 10874 - Light industrial                     | 42: Light industrial general                                                               |
|  CLASSIFICATION                    | EN 685 / EN ISO 10874 - Commercial                           | 33: Commercial heavy                                                                       |
|  CLASSIFICATION                    | EN 685 / EN ISO 10874 - Domestic                             | 23: Domestic heavy                                                                         |
|  REACTION TO FIRE                  | EN 13501-1                                                   | Bfl-S1                                                                                     |
|  STAINING RESISTANCE               | EN 438-2                                                     | Pass                                                                                       |
|  LIGHT FASTNESS                    | EN ISO 105-B02                                               | > 6                                                                                        |
|  DIMENSIONAL STABILITY             | EN 434 / EN ISO 23999                                        | ≤ 0.10 %                                                                                   |
|  ACOUSTIC IMPACT - NOISE REDUCTION | EN ISO 140-8                                                 | ΔL <sub>W</sub> =19 DB                                                                     |
|  ELECTRICAL PROPERTIES             | EN 1815                                                      | Pass                                                                                       |
|  INDENTATION - RESIDUAL            | EN ISO 24343-1                                               | ≤ 0.1 mm                                                                                   |
|  CASTOR CHAIR                      | ISO 4918                                                     | Pass                                                                                       |
|  THERMAL RESISTANCE                | EN 12667                                                     | < 0.122 (M <sup>2</sup> K/W)                                                               |
|  SLIP RESISTANCE*                  | EN 13893 / DIN 51130                                         | DS R9                                                                                      |
| WEAR RESISTANCE                                                                                                       | EN 660-2 / EN 649                                            | Class T                                                                                    |
|  IMPACT RESISTANCE                 | EN 13329                                                     | Pass                                                                                       |
|  SWELLING                          | ISO 24336                                                    | Pass                                                                                       |
|  FLOOR HEATING                     | Appropriate for standard heating systems in cement flooring. | Not appropriate for heating electric films.                                                |
| Dangerous substances                                                                                                  |                                                              |                                                                                            |
|  VOC EMISSION                      | French/Belgian/German Regulations                            | Pass                                                                                       |
|  FORMALDEHYDE - EMISSION           | EN 717 - 1                                                   | E1                                                                                         |
| REACH                                                                                                                 |                                                              | Friendly reach compliant                                                                   |
|  PCP                               | EN 12673                                                     | Pass                                                                                       |

\*Slip resistance is measured on ex-factory product. Slip resistance can be affected by surface contamination, use and how the product is maintained.  
info@rigidfloors.be - www.rigidfloors.be