Rigid WALLS by lalegno

TECHNICAL DATA SHEET
MEGA PANELS GLOSSY 5 mm

	STANDARD	RESULT
Dimensions and basic data		
SIZE	EN ISO 24342	**MEGA PANELS:** 2800 x 900 mm
THICKNESS	EN ISO 24346	5 mm
WEAR LAYER	EN ISO 24340	0.35 mm
LOCKING METHOD		T&G
SURFACE TREATMENT		PU coating + protected with aluminium oxide (anti-scratch) and stain resistant technology.
CORE		Water resistant rigid core, SPC
Technical data - CE EN 15102		
BEVELLED EDGE	MICRO	2 Sides
MASS		10.80 kg/m2
REACTION TO FIRE	EN 13501-1	B-s3,d0
LIGHT FASTNESS	EN ISO 105-B02	> 6
DIMENSIONAL STABILITY	EN 434 / EN ISO 23999	≤ 0.10 %
ELECTRICAL BEHAVIOR - BODY VOLTAGE	EN 1815	Pass
THERMAL RESISTANCE	EN 12667	<0.15 (m2K/W)
SWELLING	ISO 24336	Pass
Dangerous substances		
VOC EMISSION	French voc Regulation (iso 16000)	A+
E1 FORMALDEHYDE - EMISSION	EN 717 - 1	E1
REACH		Friendly reach compliant
RELEASE VLM/ HEAVY METALS	EN 12149	ND
SOUND ABSORPTION	EN ISO 354 / EN ISO 11654	Coëfficient: 0.05

info@rigidfloors.be - www.rigidfloors.be

Rigid WALLS by lalegno